

# 223

## Ultra High Temp Masking Tape

### DESCRIPTION

The Decker 223 is a premium grade crepe paper masking tape coated with an ultra high temperature rubber adhesive.

### FEATURE

- Applications: masking of metal surfaces under extreme heat conditions, O.E.M. assembly lines, epoxy painting applications and masking applications that require multiple heating stages
- Excellent quick stick properties and good resistance to water, solvents and oils
- Non-staining and clean removal with no residue
- Offers conformability to most surfaces
- Capable of withstanding high temperatures up to 350°F



### TECHNICAL DATA (Average Values)

Thickness	6.4 MILS
Backing	Crepe paper
Adhesive	Rubber
Tensile	24 lbs/in
Adhesion	41 oz/in
Elongation	11%
Temperature	60° TO 350°F (Duration: 30 minutes)
Color	Natural
Federal Spec.	ASTM D 6123/D 6123M-97(2012), Type I

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.