

230

Medium Grade Kraft Flatback Tape

DESCRIPTION

The Decker 230 is a smooth, flexible kraft flatback tape coated with a high tack synthetic rubber blend adhesive.

FEATURE

- Applications: carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, tabbing, bundling, reinforcing
- Excellent resistance to aging, solvents, moisture and water
- Great balance between machine and cross direction tensile and tear strength
- High tack and strong secure seal on a variety of substrates



TECHNICAL DATA (Average Values)

Thickness	7.5 MILS
Backing	Kraft Flatback
Adhesive	Synthetic Rubber Blend
Tensile	40 lbs/in
Adhesion	68 oz/in
Elongation	7%
Temperature	32° TO 200°F
Color	Kraft
Federal Spec.	PPP-T-42C, Type II C.I.D A-A-883B, Type II

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.