

434

D/C Polyester Tape

DESCRIPTION

The Decker 434 tape has polyester film coated on both sides with an aggressive solvent acrylic adhesive system.

FEATURE

- Applications: bonding metals, name plates, cloth and plastic surfaces
- Adhesive systems provides UV resistance and good aging qualities
- Heavy duty release paper allows for easy manual handling
- Works on a variety of surfaces
- Suitable to be used for indirect food contact under United States Food and Drug Administration (Code of Federal Regulations) CFR 21, section 175.105



TECHNICAL DATA (Average Values)

| | |
|-------------|-----------------|
| Thickness | 4.5 Mils |
| Backing | Polyester Film |
| Adhesive | Solvent Acrylic |
| Tensile | 20 ~ 55 lbs/in |
| Adhesion | 114 oz/in |
| Elongation | 47.5% |
| Temperature | Up TO 230°F |

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.