

Your Source For Everything Tape

est. 1969

150RT Return Tape Hot Melt Rubber

DESCRIPTION

The Decker 150RT is a polypropylene film tape coated with a hot melt rubber adhesive system on a liner. These pre-cut strips of tape are used to reseal opened packages being returned to

FEATURE

• Applications: carton re-sealing often used in the following industries - scholastic testing agencies, ink cartridge manufacturers, retail distribution centers and pharmaceutical companies

• Strong conformable film backing coupled with consistent pressure sensitive hot melt adhesive coating

• Adheres instantly to fiberboard, paper, film and a variety of surfaces

Excellent resistance to edge tear and splitting

- Strong resistance to moisture, chemicals, cold/heat and weathering
- Product can be stock or custom printed



TECHNICAL DATA (Average Values)

Thickness	1.83 Mils
Backing	BOPP
Adhesive	Hot Melt Rubber
Tensile	26 lbs/in
Adhesion	47 oz/in
Elongation	165%
Temperature	30º TO 140ºF
Color	Clear, Tan, White

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.

2 Stewart Place, Fairfield, NJ 07004 | (p) 973.227.5350 (p) 800.227.5252 | (f) 973.808.9418 www.deckertape.com