

Your Source For Everything Tape

est. 1969

150SP-18

BOPP Carton Sealing Tape Stock Printed

If Seal Is Broken

IF SEAL
IS BROKEN
CHECK CONTENTS
BEFORE ACCEPTING

IF SEAL
IS BROKEN
CHECK CONTENTS
BEFORE ACCEPTING

DESCRIPTION

The Decker 150SP-18 is a printable industrial grade polypropylene packaging tape coated with an aggressive hot melt rubber adhesive system.

FEATURE

- Applications: carton sealing, splicing, light bundling and other packaging applications
- Strong conformable film backing coupled with consistent pressure sensitive hot melt adhesive coating
- Excellent resistance to edge tear and splitting
- Resistant to moisture, chemicals, cold/heat and weathering
- ROHS compliant, meets CID A-A-1684C, complies with ASTM D 1974-92

TECHNICAL DATA (Average Values)

Thickness	1.83 Mils
Backing	ВОРР
Adhesive	Hot Melt Rubber
Tensile	26 lbs/in
Adhesion	48 oz/in
Elongation	165%
Temperature	30° TO 140°F
Color	Tan w/ Red Ink

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.

2 Stewart Place, Fairfield, NJ 07004 | (p) 973.227.5350 (p) 800.227.5252 | (f) 973.808.9418 www.deckertape.com