

322

Bi-Directional Filament Tape

DESCRIPTION

The Decker 322 is a high performance bi-directional fiberglass reinforced polypropylene tape with a synthetic rubber adhesive.

FEATURE

- Applications: reinforcing, bundling, palletizing, sealing, packaging
- Excellent adhesion, tack, quick stick bonds to most surfaces and good conformability
- High tensile strength
- Used for splicing where a high tensile strength in both MD (Machine Direction) and CD (Cross Direction) is required



TECHNICAL DATA (Average Values)

| | |
|-------------|--------------------------------|
| Thickness | 6 Mils |
| Backing | BOPP with fiberglass filaments |
| Adhesive | Synthetic Rubber |
| Tensile | 166 lbs/in |
| Adhesion | 109.63 oz/in |
| Elongation | 5% |
| Temperature | 0° TO 160°F |
| Color | Clear |

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.