

43

9 MIL Polyethylene Tape

DESCRIPTION

The Decker 43 is a heavy-duty, polyethylene film, single coated tape with a synthetic rubber pressure sensitive adhesive.

FEATURE

- Applications: all-purpose waterproof sealing applications, general industrial masking, bundling, splicing and repair applications, agricultural (greenhouse repair)
- High tack with excellent bond strength
- Good conformability and bonds well to most surfaces over a wide temperature range
- Provides a water tight seal and humidity resistance in a range of weather conditions
- Passes flame retardant requirements of NFPA and conforms to ASTM buildings material fire test E84 standards
- Product is custom printable as product 43CP



TECHNICAL DATA (Average Values)

Thickness	9 Mils
Backing	Polyethylene Film
Adhesive	Synthetic Rubber
Tensile	22 lbs/in
Adhesion	85 oz/in
Elongation	100%
Temperature	14° TO 158°F
Color	White, Clear, Yellow, Blue, Red, Black
Fire Retardant	NFPA 701 and ASTM E84 Standards

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.