

448XL

D/C Polyester Film Tape *Extended Liner*

DESCRIPTION

The Decker 448XL has polyester film coated on both sides with solvent acrylic adhesive. The lined side is coated with a low tack, semi-permanent adhesive. The exposed side is coated with a high tack, permanent clear solvent adhesive.

FEATURE

- Applications: closure method for medium to heavy weight polyethylene bags, non-woven envelopes and pouches, temporary or reusable mounting applications
- Unique adhesive allows product to be opened and resealed
- Liner side offers good removability
- Exposed side forms a long-term bond immediately upon contact
- Extended liner
- Finger lift edge



TECHNICAL DATA (Average Values)

Thickness	4 Mils
Backing	Polyester Film
Adhesive	Solvent Acrylic
Tensile	20 - 55 lbs/in
Adhesion: Liner Side	10 - 17 oz/in
Adhesion: Exposed Side	58 - 74 oz/in
Elongation	47.5 - 52.5%
Temperature	Up TO 194°F
Color	White release liner

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.