

# 520-3

## PTFE Coated Glass Tape

### DESCRIPTION

The Decker 520-3 is a PTFE coated fiberglass tape designed to operate in demanding temperatures and chemical environments.

### FEATURE

- Applications: used in a variety of industries including aerospace, electronics and packaging
- Suited for use on packaging equipment, chute liners, wire and cable insulation
- Excellent tear resistance, exceptional strength and durability



### TECHNICAL DATA (Average Values)

|             |                                      |
|-------------|--------------------------------------|
| Thickness   | 3 Mils (Substrate) 2 Mils (Adhesive) |
| Substrate   | Woven Fiberglass                     |
| Coating     | PTFE                                 |
| Adhesive    | Silicone                             |
| Tensile     | 55 lbs/in                            |
| Adhesion    | 40 oz/in                             |
| Elongation  | 3%                                   |
| Temperature | 500°F (Max Operating Temp)           |

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.