

530-5

5 Mil Polyimide Film Tape

DESCRIPTION

The Decker 530-5 is a thin strong polyimide film tape coated with a high performance silicone adhesive that has superior temperature resistance.

FEATURE

- Applications: widely used to protect gold contact fingers on printed circuit boards during wave solder applications; insulation for electrical coils, transformers, motor and other electrical components
- Continually performs in temperatures up to 500°F
- High dielectric strength
- RoHs Compliant



TECHNICAL DATA (Average Values)

| | |
|-----------------|--|
| Total Thickness | 6.5 MILS |
| Backing | HN Polyimide Film |
| Adhesive | Silicone |
| Tensile | 98 lbs/in |
| Adhesion | 25 oz/in |
| Elongation | 65% |
| Temperature | -100°F to 500°F |
| Color | Amber |
| Federal Spec. | Mil-P-46112B/ASTM D 5213, Type 1, Item A |

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.