

# 77-I

## Polyester Powder Coating Tape

### DESCRIPTION

The Decker 77-I is a polyester film tape coated with a specifically cured silicone adhesive system designed for high performance, high temperature resistance.

### FEATURE

- Applications: high temperature applications, such as powder coating, E-coating, anodizing and photo splicing
- Excellent resistance to acid, oils, solvents and staining
- Silicone adhesive can withstand bake cycle temperatures up to 400°F and still remove cleanly
- Product can be custom die-cut to specifications
- Dielectric strength 7000 volts
- Product compliant with European Union's RoHs initiative and with European REACH regulation



### TECHNICAL DATA (Average Values)

Thickness	3.5 Mils
Backing	Polyester Film - 2 mils
Adhesive	Silicone
Tensile	50 lbs/in
Adhesion	30 oz/in
Elongation	100%
Temperature	-99.4° TO 392°F
Color	Green

This Technical Data Sheet (TDS) is provided by Decker Tape for information purposes only. The contents of this TDS are considered reliable but accuracy is not guaranteed. This data is of average values and does not constitute a warranty of fitness for a particular purpose. The user is required to determine the suitability for this purpose, by test or otherwise. Any liability arising in respect of our products, including consequential, will be limited to the value of those products charged to the customer excluding any consequential loss. We reserve the right to make changes without notice or obligation in our products and publications.